



**Sourcing
Industrial
de México**

**VÁLVULAS
CATÁLOGO
2023**



VALVES

FULL PORT - BALL VALVES



STAINLESS STEEL


| SIZES | 1/2" - 10" | |
|-----------|--|-----------|
| | CLASS | FIGURE # |
| PRESSURES | 150 | 266F150 |
| | 150 | 266F150DM |
| | 300 | 266F300 |
| MATERIAL | CF8M | |
| ENDS | Flanged | |
| TRIM | TFM 1600 Seats; PTFE Packing | |
| FEATURES | Locking Device; ISO 5211 Mounting Pad. Pressure Relief Vent on Ball; Lever & Worm Gears | |

CARBON STEEL

| SIZES | 1/2" - 10" | |
|-----------|--|----------|
| | CLASS | FIGURE # |
| PRESSURES | 150 | 256F150 |
| | 300 | 256F300 |
| MATERIAL | A216 WCB | |
| ENDS | Flanged | |
| TRIM | TFM 1600 Seats; 316 Stainless Steel Trim; PTFE Packing | |
| FEATURES | Locking Device; ISO 5211 Mounting Pad. Pressure Relief Vent on Ball; Lever & Worm Gears | |

FULL PORT - BALL VALVES

FIRE SAFE



STAINLESS STEEL

| SIZES | 1/2" - 12" | |
|-----------|---|-----------|
| | CLASS | FIGURE # |
| PRESSURES | 150 | 266F150FS |
| | 300 | 266F300FS |
| | 600 | 266F600FS |
| MATERIAL | CF8M | |
| ENDS | Flanged | |
| TRIMS | TFM 1600 Seats; Low-Emission Graphite Packing - 100ppm; NACE - MR0103; API 607 Fire-Safe Design | |
| FEATURES | Locking Device; ISO 5211 Mounting Pad; Anti-Static Device; Pressure Relief Vent on Ball; Lever & Worm Gear. HNBRO-Rings on all 600# design. | |

CARBON STEEL

| SIZES | 1/2" - 12" | |
|-----------|---|-----------|
| | CLASS | FIGURE # |
| PRESSURES | 150 | 256F150FS |
| | 300 | 256F300FS |
| | 600 | 256F600FS |
| MATERIAL | A216 WCB | |
| ENDS | Flanged | |
| TRIMS | TFM 1600 Seats; 316 Stainless Steel Trim; Low-Emission Graphite Packing - 100ppm; NACE - MR0103; API 607 Fire Safe Design | |
| FEATURES | Locking Device; ISO 5211 Mounting Pad; Anti-Static Device; Pressure Relief Vent on Ball; Lever & Worm Gear. HNBRO-Rings on all 600# design. | |



VALVES

REDUCED PORT - BALL VALVES

FIRE SAFE




STAINLESS STEEL

| SIZES | 1/2" - 6" | |
|-----------|---|-----------|
| | CLASS | FIGURE # |
| PRESSURES | 150 | 166R150FS |
| MATERIAL | CF8M | |
| ENDS | Flanged | |
| TRIM | TFM 1600 Seats; Low-Emission Graphite Packing - 100ppm; NACE - MR0103; API 607 Fire Safe Design | |
| FEATURES | Locking Device; ISO 5211 Mounting Pad; Anti-Static Device; Pressure Relief Vent on Ball; Lever & Worm Gear; Uni-body design | |

CARBON STEEL

| SIZES | 1/2" - 6" | |
|-----------|---|-----------|
| | CLASS | FIGURE # |
| PRESSURES | 150 | 156R150FS |
| MATERIAL | A216 WCB | |
| ENDS | Flanged | |
| TRIM | TFM 1600 Seats; 316 Stainless Steel Trim; Low-Emission Graphite Packing - 100ppm; NACE - MR0103; API 607 Fire Safe Design | |
| FEATURES | Locking Device; ISO 5211 Mounting Pad; Anti-Static Device; Pressure Relief Vent on Ball; Lever & Worm Gear; Uni-body design | |

WAY FULL PORT - BALL VALVES




STAINLESS STEEL

| SIZES | 1/2" - 4" | |
|-----------|---|------------|
| | CLASS | FIGURE # |
| PRESSURES | 150 | 3T66F150DM |
| | 150 | 3L66F150DM |
| MATERIAL | CF8M | |
| ENDS | Flanged | |
| PORTS | T-Port & L-Port | |
| TRIM | RTFE Seats; RTFE Packing; Viton™ O-Rings | |
| FEATURES | Locking Device; ISO 5211 Direct Mounting Pad; Lever | |



VALVES

REDUCED PORT 1-PC- BALL VALVES



STAINLESS STEEL & CARBON STEEL

| SIZES | 1/4" - 2" | |
|-----------|--|----------|
| | CLASS | FIGURE # |
| PRESSURES | 1000 WOG | 166RT |
| | 1000 WOG | 156RT |
| MATERIAL | CF8M & WCB | |
| ENDS | Threaded | |
| TRIM | 316 Stainless Steel Trim; PTFE Packing; RTFE Seats | |
| FEATURES | Slide Latch Locking Device; 150 PSIG Saturated Steam Rating | |

FULL PORT 2-PC- BALL VALVES



STAINLESS STEEL & CARBON STEEL

| SIZES | 1/4" - 4" | |
|-----------|---|----------|
| | CLASS | FIGURE # |
| PRESSURES | 1000 WOG | 266FTS |
| | 1000 WOG | 256FTS |
| MATERIAL | CF8M & WCB | |
| ENDS | Threaded | |
| TRIM | 316 Stainless Steel Trim; PTFE Packing & Seal; RTFE Seats | |
| FEATURES | Slide Latch Locking Device; Oval Handwheels Available Upon Request; 150 PSIG Saturated Steam Rating | |

FULL PORT 2-PC- BALL VALVES



STAINLESS STEEL & CARBON STEEL

| SIZES | 1/4" - 2" | |
|-----------|---|----------|
| | CLASS | FIGURE # |
| PRESSURES | 2000-1500 WOG | 266FT |
| | 2000-1500 WOG | 256FT |
| MATERIAL | CF8M & WCB | |
| ENDS | Threaded | |
| TRIM | 316 Stainless Steel Trim; PTFE Packing & Seal; RTFE Seats | |
| FEATURES | Slide Latch Locking Device; Oval Handwheels Available Upon Request; 150 PSIG Saturated Steam Rating | |

SIZES CLASS FIGURE #

FULL PORT 2-PC- SEALWELDED BODY



STAINLESS STEEL & CARBON STEEL

| SIZES | 1/4" - 2" | |
|-----------|---|----------|
| | CLASS | FIGURE # |
| PRESSURES | 2000-1500 WOG | 266FT |
| | 2000-1500 WOG | 256FT |
| MATERIAL | CF8M & WCB | |
| ENDS | Threaded | |
| TRIM | 316 Stainless Steel Trim; PTFE Packing & Seal; RTFE Seats | |
| FEATURES | Slide Latch Locking Device; Oval Handwheels Available Upon Request; 150 PSIG Saturated Steam Rating | |

SIZES



VALVES

FULL PORT 2-PC- SEALWELDED BODY

FIRE SAFE



STAINLESS STEEL

| SIZES | 1/4" - 2" | |
|-----------|---|-------------|
| | CLASS | FIGURE # |
| PRESSURES | 2000-1500 WOG | 266FTW (FS) |
| MATERIAL | CF8M | |
| ENDS | Threaded | |
| TRIM | 316 Stainless Steel Trim; Graphite Packing; RTFE Seats | |
| FEATURES | Slide Latch Locking Device; Fire Safe; NACE MR0175; Oval Handwheels Available Upon Request; 150 PSIG Saturated Steam Rating | |

FULL PORT 2-PC- BRASS BALL VALVES



FORGED BRASS

| SIZES | 1/4" - 4" | |
|-----------|--|---------------------|
| | CLASS | FIGURE # |
| PRESSURES | 600 WOG | 200BRFTLH |
| | 600 WOG | 200BRFT 2 1/2" - 4" |
| MATERIAL | Brass | |
| ENDS | Threaded | |
| TRIM | Brass Stem; Chrome Plated Copper Ball; PTFE Packing & Seats | |
| FEATURES | 150 PSIG Saturated Steam Rating; UL & CSA Listed up through 2" @ 400 WOG; Up through 4" Rated @ 250 WOG; Slide Latch Locking Device through 2" | |

FULL PORT 3-PC- BALL VALVES



STAINLESS STEEL & CARBON STEEL

| SIZES | 1/4" - 2" | |
|-----------|--|-------------------------|
| | CLASS | FIGURE # |
| PRESSURES | 1000 WOG | 366FT & 366FW & 366FTxS |
| | 1000 WOG | 356FT & 356FW & 356FTxS |
| MATERIAL | CF8M & WCB | |
| ENDS | Threaded & Socketweld & THD x SWE | |
| TRIM | 316 Stainless Steel Trim; PTFE Packing & Seal; RTFE Seats | |
| FEATURES | Slide Latch Locking Device; ISO 5211 Mounting Pad; 150 PSIG Saturated Steam Rating | |

FULL PORT 3-PC- BALL VALVES



STAINLESS STEEL & CARBON STEEL

| SIZES | 1/4" - 4" | |
|-----------|--|---------------|
| | CLASS | FIGURE # |
| PRESSURES | 1000 WOG | 366FT & 366FW |
| | 1000 WOG | 356FT & 356FW |
| MATERIAL | CF8M & WCB | |
| ENDS | Threaded & Socketweld | |
| TRIM | 316 Stainless Steel Trim; PTFE Packing & Seal; RTFE Seats | |
| FEATURES | Slide Latch Locking Device; ISO 5211 Mounting Pad; 150 PSIG Saturated Steam Rating | |



VALVES


FULL PORT 3-PC- BALL VALVES **FIRE SAFE**



STAINLESS & CARBON STEEL

| SIZES | 1/4" - 2" | |
|-----------|--|----------------------------|
| | CLASS | FIGURE # |
| PRESSURES | 2000-1500 WOG | 2366FT & 2366FW & 2366FTxS |
| | 2000-1500 WOG | 2356FT & 2356FW & 2356FTxS |
| MATERIAL | CF8M & WCB | |
| ENDS | Threaded & Socketweld & THD x SWE | |
| TRIM | 316 Stainless Steel Trim; Graphite Packing & Gasket; RTFE Seats | |
| FEATURES | Slide Latch Locking Device; Fire Safe; NACE MR0175; ISO 5211 Mounting Pad; 150 PSIG Saturated Steam Rating | |

FULL PORT 3-PC- PEEK SEATED BALL VALVES **FIRE SAFE**



STAINLESS & CARBON STEEL

| SIZES | 1/4" - 2" | |
|-----------|--|-------------------|
| | CLASS | FIGURE # |
| PRESSURES | 2000-1500 WOG | 2366FTP & 2366FWP |
| | 2000-1500 WOG | 2356FTP & 2356FWP |
| MATERIAL | CF8M & WCB | |
| ENDS | Threaded & Socketweld | |
| TRIM | 316 Stainless Steel Trim; Graphite Packing & Gasket; PEEK Seats good up to 600° F | |
| FEATURES | Slide Latch Locking Device; Fire Safe; NACE MR0175; ISO 5211 Mounting Pad; 150 PSIG Saturated Steam Rating | |

FULL PORT 2-PC FS SEALWELDED BODY **FIRE SAFE**



STAINLESS STEEL & CARBON STEEL

| SIZES | 1/4" - 2" | |
|-----------|--|------------------|
| | CLASS | FIGURE # |
| PRESSURES | 3600 WOG | 3266HP & 3266HPW |
| | 3600 WOG | 3256HP & 3256HPW |
| | 6000 WOG | 6266HP |
| | 6000 WOG | 6256HP |
| MATERIAL | CF8M & WCB | |
| ENDS | Threaded & Socketweld | |
| TRIM | Sealwelded Body Design; 316 Stainless Steel Trim; Graphite Packing & Seal; PEEK Seats | |
| FEATURES | Slide Latch Locking Device; Fire Safe; NACE MR0175; ISO 5211 Mounting Pad; 250 PSIG Saturated Steam Rating | |

REDUCED PORT 3-WAY BALL VALVES



STAINLESS STEEL

| SIZES | 1/4" - 2" | |
|-----------|---|----------|
| | CLASS | FIGURE # |
| PRESSURES | 1000 WOG | 3T66RTDM |
| | 1000 WOG | 3L66RTDM |
| MATERIAL | CF8M | |
| ENDS | Threaded | |
| PORTS | T-Port & L-Port | |
| TRIM | RTFE Seats; PTFE Packing & Gasket; Viton™ O-Rings | |
| FEATURES | Slide Latch Locking Device; ISO 5211 Direct Mounting Pad; Pressure Relief Vent on Ball; 150 PSIG Saturated Steam Rating | |



VALVES

FULL PORT 2-PC DIRECT MOUNT BALL VALVES



STAINLESS STEEL

| SIZES | 1/4" - 2" | |
|-----------|---|----------|
| | CLASS | FIGURE # |
| PRESSURES | 1000 WOG | 266FTDM |
| MATERIAL | CF8M & WCB | |
| ENDS | Threaded | |
| TRIM | 316 Stainless Steel Trim; PTFE Packing & Seal; TFM 1600 Seats; Viton™ O-Ring | |
| FEATURES | ISO 5211 Direct Mounting Pad; Anti-Static Device; 150 PSIG Saturated Steam Rating | |

FULL PORT 3-PC DIRECT MOUNT BALL VALVES



STAINLESS STEEL

| SIZES | 1/4" - 4" | |
|-----------|---|----------|
| | CLASS | FIGURE # |
| PRESSURES | 1000 WOG | 366FTDM |
| | 1000 WOG | 366FWDM |
| MATERIAL | CF8M | |
| ENDS | Threaded & Socketweld | |
| TRIM | 316 Stainless Steel Trim; PTFE Packing & Gasket; TFM 1600 Seats; Viton™ O-Ring | |
| FEATURES | ISO 5211 Direct Mounting Pad; Anti-Static Device; 150 PSIG Saturated Steam Rating | |

TRUNNION MOUNTED BALL VALVES

FIRE SAFE



STAINLESS STEEL & CARBON STEEL

| SIZES | 2" - 24" | | | |
|----------------|--|-------------------|-------------------|--------------------|
| | CLASS | CS X EPN FIGURE # | CS X 316 FIGURE # | 316 X 316 FIGURE # |
| PRESSURES | 150 | 29FEFDHTR150FS | 29F6FDHTR150FS | 28F6FPTTR150FS |
| | | 39FEFDHTR150FS | 39F6FDHTR150FS | 38F6FPTTR150FS |
| | 300 | 29FEFDHTR300FS | 29F6FDHTR300FS | 28F6FPTTR300FS |
| 39FEFDHTR300FS | | 39F6FDHTR300FS | 38F6FPTTR300FS | |
| 600 | 39FEFDHTR600FS | 39F6FDHTR600FS | 38F6FPTTR600FS | |
| MATERIAL | A105N/LF2 x ENP; A105N/LF2 x 316; A182-F316 x 316 | | | |
| ENDS | RF, BW, RTJ | | | |
| TRIM | 3 Mil ENP; 316 Stainless Steel; Devlon®, PEEK Seats; HNBR, Teflon™ Lip Seals O-Rings; Graphite Packing | | | |
| FEATURES | API-6D; DBB to API-6D; Fire Safe to API 607; NACE to MR0103 & MR0175; Low Emission to API 622 -100 ppm; Emergency Grease Injector Fittings | | | |



VALVES

200 WOG THREADED GG&C VALVES



STAINLESS STEEL

| SIZES | 1/4" - 3" | |
|-----------|--------------------------|----------|
| | CLASS | FIGURE # |
| PRESSURES | 200 WOG | SS200GT |
| | 200 WOG | SS200GL |
| | 200 WOG | SS200CK |
| MATERIAL | CF8M | |
| TRIM | Threaded | |
| FEATURES | 316 Stainless Steel Trim | |

STANDARD PORT FORGED GG&C VALVES



STAINLESS STEEL

| SIZES | 1/4" - 2" | |
|------------|--|----------|
| | CLASS | FIGURE # |
| PRESSURES | 1000 WOG | 366FTDM |
| | 1000 WOG | 366FWDM |
| CONNECTION | CF8M | |
| MATERIAL | Threaded & Socketweld | |
| ENDS | 316 Stainless Steel Trim; PTFE Packing & Gasket; TFM 1600 Seats; Viton™ O-Ring | |
| TRIM | ISO 5211 Direct Mounting Pad; Anti-Static Device; 150 PSIG Saturated Steam Rating Graphite Packing & Gasket to API 622 Low-Emission - 100ppm | |
| FEATURES | API 602 Design Standard | |

STANDARD PORT FORGED GG&C VALVES



STAINLESS STEEL

| SIZES | 1/4" - 2" | |
|------------|---|----------|
| | CLASS | FIGURE # |
| PRESSURES | 1000 WOG | 366FTDM |
| | 1000 WOG | 366FWDM |
| CONNECTION | CF8M | |
| MATERIAL | Threaded & Socketweld | |
| ENDS | 316 Stainless Steel Trim; PTFE Packing & Gasket; TFM 1600 Seats; Viton™ O-Ring | |
| TRIM | ISO 5211 Direct Mounting Pad; Anti-Static Device; 150 PSIG Saturated Steam Rating API Trim 8; NACE MR0103 & MR0175; Graphite Packing & Gasket to API 622 Low-Emission - 100ppm | |
| FEATURES | API 602 Design Standard | |



200 WOG THREADED GG&C VALVES



STAINLESS STEEL

| SIZES | 1/4" - 3" | |
|-----------|--------------------------|----------|
| | CLASS | FIGURE # |
| PRESSURES | 200 WOG | SS200GT |
| | 200 WOG | SS200GL |
| | 200 WOG | SS200CK |
| MATERIAL | CF8M | |
| ENDS | Threaded | |
| TRIM | 316 Stainless Steel Trim | |

STANDARD PORT FORGED GG&C VALVES



STAINLESS STEEL

| SIZES | 1/4" - 2" | |
|------------|---|-----------------------|
| | CLASS | FIGURE # |
| PRESSURES | 800# | GASS800TE & GASS800SW |
| | 800# | GLSS800TE & GLSS800SW |
| | 800# | SCSS800TE & SCSS800SW |
| | 800# | PCSS800TE & PCSS800SW |
| CONNECTION | Bolted Bonnet | |
| MATERIAL | A182 F316L | |
| ENDS | Threaded & Socketweld | |
| TRIM | API Trim 12; NACE MR0103 & MR0175; Graphite Packing & Gasket to API 622 Low-Emission - 100ppm | |
| FEATURES | API 602 Design Standard | |

STANDARD PORT FORGED GG&C VALVES



MATERIAL


CARBON STEEL

| SIZES | 1/4" - 2" | |
|------------|--|---------------------------------|
| | CLASS | FIGURE # |
| PRESSURES | 800# | GAN800TE & GAN800SW & GAN800TXS |
| | 800# | GLN800TE & GLN800SW |
| | 800# | SCN800TE & SCN800SW |
| | 800# | PCN800TE & PCN800SW |
| CONNECTION | Bolted Bonnet | |
| MATERIAL | A105N | |
| ENDS | Threaded & Socketweld & THD x SWE | |
| TRIM | API Trim 8; NACE MR0103 & MR0175; Graphite Packing & Gasket to API 622 Low-Emission - 100ppm | |
| FEATURES | API 602 Design Standard | |



GATE, GLOBE & CHECK VALVES

STANDARD PORT FORGED FLANGED END GG&C VALVES



CARBON STEEL

| SIZES | 1/4" - 2" | |
|------------|--|----------|
| | CLASS | FIGURE # |
| PRESSURES | 150# | GAN150FE |
| | 150# | GLN150FE |
| | 150# | SCN150FE |
| | 150# | PCN150FE |
| | 300# | GAN300FE |
| | 300# | GLN300FE |
| | 300# | SCN300FE |
| CONNECTION | Bolted Bonnet | |
| MATERIAL | A105N | |
| ENDS | Flanged | |
| TRIM | API Trim 8; NACE MR0103 & MR0175; Graphite Packing & Gasket to API 622 Low-Emission - 100ppm | |
| FEATURES | API 602 Design Standard | |

API 603 - CAST GATE, GLOBE & SWING CHECK VALVES



MATERIAL

STAINLESS STEEL

| SIZES | CLASS | 1/2" - 24" | |
|------------|---|------------|------------|
| | | TEFLON® | GRAPHITE |
| PRESSURES | 150# | SSN150GT | SSN150GRGT |
| | 150# | SSN150GL | SSN150GRGL |
| | 150# | SSN150CK | SSN150GRCK |
| | 300# | SSN300GT | SSN300GRGT |
| | 300# | SSN300GL | SSN300GRGL |
| | 300# | SSN300CK | SSN300GRCK |
| CONNECTION | Bolted Bonnet | | |
| MATERIAL | CF8M | | |
| ENDS | Flanged | | |
| TRIM | API Trim 10; 150# 8" & Larger API Trim 12; 300# 6" & Larger API Trim 12; NACE MR0103 & MR0175; Low-Emission to API 622 - 100ppm | | |
| FEATURES | API 603 Design Standard; Available in both Teflon® Packing & Gasket and Graphite Packing & Gasket | | |



VALVES

API 600 - CAST GATE, GLOBE & SWING CHECK VALVES

STAINLESS STEEL

| SIZES | 2" - 36" | |
|------------|---|-------------|
| | CLASS | FIGURE # |
| PRESSURES | 600# | SSN600GRGT |
| | 600# | SSN600GRGL |
| | 600# | SSN600GRCK |
| | 900# | SSN900GRGT |
| | 900# | SSN900GRGL |
| | 900# | SSN900GRCK |
| | 1500# | SSN1500GRGT |
| | 1500# | SSN1500GRGL |
| CONNECTION | Bolted Bonnet | |
| MATERIAL | CF8M | |
| ENDS | Flanged | |
| TRIM | API Trim 12; NACE MR0103 & MR0175; Graphite Packing & Gasket in accordance to API 622 Low-Emission - 100ppm | |
| FEATURES | API 600 Design Standard | |



API 600 - CAST GATE, GLOBE & SWING CHECK VALVES


CARBON STEEL

| SIZES | 2" - 36" | |
|------------|--|------------|
| | CLASS | FIGURE # |
| PRESSURES | 150# | CSN150GT |
| | 150# | CSN150GTGO |
| | 150# | CSN150GL |
| | 150# | CSN150CK |
| | 300# | CSN300GT |
| | 300# | CSN300GTGO |
| | 300# | CSN300GL |
| | 300# | CSN300CK |
| | 600# | CSN600GT |
| | 600# | CSN600GTGO |
| | 600# | CSN600GL |
| | 600# | CSN600CK |
| CONNECTION | Bolted Bonnet | |
| MATERIAL | A216 WCB | |
| ENDS | Flanged | |
| TRIM | API Trim 8; NACE MR0103 & MR0175; Graphite Packing & Gasket in accordance to API 622 Low-Emission - 100ppm | |
| FEATURES | API 600-623-594 Design Standards; 8" and Larger Gates available with Bevel Gears Operators | |



HIGH PERFORMANCE BUTTERFLY - DOUBLE OFF - SET

FIRE SAFE
NON FIRE SAFE



STAINLESS STEEL

| SIZES | 2" - 36" | |
|-----------|---|---------------------------|
| | CLASS | FIGURE # |
| PRESSURES | 150# | HPSS150LL & HPSS150LG |
| | 150# | HPSS150LLFS & HPSS150LGFS |
| | 300# | HPSS300LL & HPSS300LG |
| | 300# | HPSS300LLFS & HPSS300LGFS |
| MATERIAL | CF8M | |
| ENDS | Lug | |
| TRIM | 316 Stainless Steel Trim; Non Fire Safe & Fire Safe Design; PTFE+316 SS Seats and RTFE Soft Seats; NACE MRO175; Low-Emission - 50 ppm | |
| FEATURES | API 609 Design Standards; Lever & Gear Oper.; Dead End Service | |

HIGH PERFORMANCE BUTTERFLY - DOUBLE OFF - SET

FIRE SAFE
NON FIRE SAFE



CARBON STEEL

| SIZES | 2" - 36" | |
|-----------|---|---------------------------|
| | CLASS | FIGURE # |
| PRESSURES | 150# | HPCS150LL & HPCS150LG |
| | 150# | HPCS150LLFS & HPCS150LGFS |
| | 300# | HPCS300LL & HPCS300LG |
| | 300# | HPCS300LLFS & HPCS300LGFS |
| MATERIAL | A216 WCB | |
| ENDS | Lug | |
| TRIM | 316 Stainless Steel Trim; Non Fire Safe & Fire Safe Design; PTFE+316 SS Seats and RTFE Soft Seats; NACE MRO175; Low-Emission - 50 ppm | |
| FEATURES | API 609 Design Standards; Lever & Gear Oper.; Dead End Service | |



BUTTERFLY VALVES

RESILIENT SEATED BUTTERFLY VALVES



DUCTIL IRON

| SIZES | 2" - 36" | |
|-----------|--|----------|
| | CLASS | FIGURE # |
| PRESSURES | 200# & 150# | 4800 |
| | 200# & 150# | 4100 |
| MATERIAL | Ductile Iron | |
| ENDS | Lug & Wafer | |
| TRIM | Disc: Ni-Coated Ductile Iron; 316 Stainless; Bronze Seats: EPDM; Buna-N; Teflon; Viton 416 Stainless Steel Stem | |
| FEATURES | API 609 Design Standard; Lever & Gear Oper.; 2" - 12" 200 PSI 14" - 24" 150 PSI; Dead End Service; All Teflon™ Seated Valves 150 PSI | |

RESILIENT SEATED - SHORT NECK BUTTERFLY VALVES



DUCTIL IRON

| SIZES | 2" - 12" | |
|-----------|---|----------|
| | CLASS | FIGURE # |
| PRESSURES | 200# | 6800 |
| | 200# | 6100 |
| MATERIAL | Ductile Iron | |
| ENDS | Lug & Wafer | |
| TRIM | Disc: Ni-Coated Ductile Iron; 316 Stainless; Bronze Seats: EPDM; Buna-N; Teflon™; Viton® 416 Stainless Steel Stem | |
| FEATURES | API 609 Design Standard; Lever & Gear Oper.; Double "D" Stem | |

